



HDMI™ Matrix-Switch | 4 x 2-Poorts poort(en) | 4x HDMI™ Input | 2x 3,5 mm / 2x HDMI™ Output / 2x TosLink | 4K@60Hz | 18 Gbps | Afstandbestuurbaar | Metaal | Antraciet



Productspecificaties VMAT3482AT:

Aantal producten in verpakking	1 Stuks		YCbCr 4:4:4		
Afstandbestuurbaar	Ja	Klokfrequentie	0 MHz		DTS-HD
Apparaat stroominput	DC 9 x 5,5 mm	Materiaal	Metaal		DTS-HD-Master Audio
Bandbreedte	600 mHz	Maximale bandbreedte	18 Gbps		EDlie
Controlerende methode	Afstandsbediening	Maximale resolutie	4K@60Hz		HDCP
		Ondersteunde resoluties	1080i		LPCM
			1080p	Output	2x 3,5 mm
	Manueel		480i		2x HDMI™ Output
EDID-instellingen	Auto		480p		2x TosLink
	HDCP 2.2		4K@30Hz	Poorten	4 x 2-Poorts poort(en)
	Compatible		4K@60Hz		Euro / Type-C (CEE 7/16)
Ingangsstroom	2 A		576i		
Ingangsvoltage	5 V DC		576p		
Input	4x HDMI™ Input	Ondersteunde technologie	720p	Stekkertype	
Kabellengte voedingsadapter	1.0 m			Stroomverbruik in standby-modus	1 W
Kleur	Antraciet			Stroomverbruik indien ingeschakeld	5 W
Kleurformaten	RGB			Type apparaat	HDMI™-Matrix-Switch
	YCbCr 4:2:0				
	YCbCr 4:2:2				

Verpakkingsinformatie:

Merk	Nedis
Ordercode	VMAT3482AT
EAN single Product	5412810337231
EAN Inner Carton	
EAN Outer Carton	5412810337248
Verpakking	Box
Inhoud verpakking	HDMI™ matrix
	Voedingsadapter 5 V DC - 2 A

Lees meer online

Aantal	L x	B x	H(mm)	Gewicht
1	215 mm	55 mm	290 mm	1020 g
10	310 mm	235 mm	550 mm	10980 g

