



CAT7 nettverkskabel | S/FTP | RJ45 Han | RJ45 Han | 5.00 m | Snagless | Rund | LSZH | Hvit | Konvolutt



Produktspesifikasjoner CCGP85420WT50:

|                           |             |          |    |
|---------------------------|-------------|----------|----|
| Antall produkter i pakken | 1 stk.      | Snagless | Ja |
| AWG-verdi                 | 26          |          |    |
| Emballasjetype            | Konvolutt   |          |    |
| Farge                     | Hvit        |          |    |
| Frekvens                  | 600 MHz     |          |    |
| Kabel mantelen materialet | LSZH        |          |    |
| Kabellengde               | 5.00 m      |          |    |
| Kabelmantelstørrelse      | 5.8 mm      |          |    |
| Kabeltype                 | CAT7        |          |    |
| Kabelutforming            | Rund        |          |    |
| Koblingsbelegg            | Gull belagt |          |    |
| Kontakt A                 | RJ45 Han    |          |    |
| Kontakt B                 | RJ45 Han    |          |    |
| Kontaktutforming – side A | Rett        |          |    |
| Kontaktutforming – side B | Rett        |          |    |
| Ledermateriale            | Kobber      |          |    |
| Makimum båndbredde        | 10 Gbps     |          |    |
| Skjerming                 | S/FTP       |          |    |

Informasjon om emballasje:

|                    |                            |
|--------------------|----------------------------|
| Merke              | Nedis                      |
| Bestill koden      | CCGP85420WT50              |
| EAN single Product | 5412810349104              |
| EAN Inner Carton   | 5412810408771              |
| EAN Outer Carton   | 5412810349364              |
| Emballasje         | Envelope                   |
| Innholdet i pakken | 1x PiMF CAT7 Network Cable |

| Antall | L x    | B x    | H(mm)  | Vekt   |
|--------|--------|--------|--------|--------|
| 1      | 40 mm  | 230 mm | 130 mm | 189 g  |
| 20     | 310 mm | 150 mm | 430 mm | 4100 g |
| 40     | 325 mm | 310 mm | 450 mm | 8760 g |

