



CAT5e nettverkskabel | U/UTP | RJ45 Han | RJ45 Han | 2.00 m | Rund | PVC | Sort | Label



Produktspesifikasjoner CCGL85100BK20:

|                           |             |           |       |
|---------------------------|-------------|-----------|-------|
| Antall produkter i pakken | 1 stk.      | Skjerming | U/UTP |
| AWG-verdi                 | 26          | Snagless  | Nei   |
| Emballasjetype            | Label       | Versjon   | 1:1   |
| Farge                     | Sort        |           |       |
| Frekvens                  | 100 MHz     |           |       |
| Kabel mantelen materialet | PVC         |           |       |
| Kabellengde               | 2.00 m      |           |       |
| Kabelmantelstørrelse      | 5.0 mm      |           |       |
| Kabeltype                 | CAT5e       |           |       |
| Kabelutforming            | Rund        |           |       |
| Koblingsbelegg            | Gull belagt |           |       |
| Kontakt A                 | RJ45 Han    |           |       |
| Kontakt B                 | RJ45 Han    |           |       |
| Kontaktutforming – side A | Rett        |           |       |
| Kontaktutforming – side B | Rett        |           |       |
| Ledermateriale            | Kobber      |           |       |
| Makimum båndbredde        | 1 Gbps      |           |       |
| Materiale                 | PVC         |           |       |

Informasjon om emballasje:

|                    |                            |
|--------------------|----------------------------|
| Merke              | Nedis                      |
| Bestill koden      | CCGL85100BK20              |
| EAN single Product | 5412810422388              |
| EAN Inner Carton   | 5412810429790              |
| EAN Outer Carton   | 5412810434312              |
| Emballasje         | Label                      |
| Innholdet i pakken | 1x UTP CAT5e Network Cable |

| Antall | L x    | B x    | H(mm)  | Vekt   |
|--------|--------|--------|--------|--------|
| 60     | 190 mm | 280 mm | 280 mm | 3620 g |
| 120    | 300 mm | 300 mm | 400 mm | 7800 g |

